

(19) 世界知的所有権機関
国際事務局(43) 国際公開日
2000年12月28日 (28.12.2000)

PCT

(10) 国際公開番号
WO 00/78464 A1

(51) 国際特許分類: B04B 1/02, 7/08, 11/05, G01N 35/00

(21) 国際出願番号: PCT/JP99/03341

(22) 国際出願日: 1999年6月23日 (23.06.1999)

(25) 国際出願の言語: 日本語

(26) 国際公開の言語: 日本語

(71) 出願人(米国を除く全ての指定国について): 株式会社日立製作所(HITACHI, LTD.) [JP/JP]; 〒101-8010 東京都千代田区神田駿河台四丁目6番地 Tokyo (JP).

(72) 発明者: および

(75) 発明者/出願人(米国についてのみ): 岡野和宣(OKANO, Kazunori) [JP/JP], 村川克二(MURAKAWA, Katsuji) [JP/JP]; 〒185-8601 東京都国分寺市東恋ヶ窪

一丁目280番地 株式会社日立製作所 中央研究所内 Tokyo (JP). 福岡真一(FUKUZONO, Shinichi) [JP/JP]; 〒312-0033 茨城県ひたちなか市市毛882番地 株式会社日立製作所 計測器事業部内 Ibaraki (JP). 池田由紀子(IKEDA, Yukiko) [JP/JP]; 〒300-0013 茨城県土浦市神立町502番地 株式会社日立製作所 機械研究所内 Ibaraki (JP).

(74) 代理人: 弁理士 作田康夫(SAKUTA, Yasuo); 〒100-8220 東京都千代田区丸の内一丁目5番1号 株式会社日立製作所内 Tokyo (JP).

(81) 指定国(国内): CN, JP, KR, US.

(84) 指定国(広域): ヨーロッパ特許(AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).


添付公開書類:

— 国際調査報告書

/続葉有/

(54) Title: CENTRIFUGAL SEPARATOR AND SAMPLE PREPARATION DEVICE USING THE SEPARATOR

(54) 発明の名称: 遠心分離機及びこれを用いる試料調製装置



(57) Abstract: A centrifugal separator, comprising a centrifugal rotor (10-1) having a sample separating chamber (2) for centrifugally separating samples contained in a sample solution provided therein, an upper part opening (3) leading to the sample separating chamber provided at the upper part thereof and rotationally symmetrical axis, a member connectable to the opening, and a rotationally driving means which rotates the member so as to rotate the centrifugal rotor about a rotating axis in the first direction with the direction of the rotationally symmetrical axis assumed to be the first direction, wherein, when two directions crossing perpendicular to the first direction are assumed to be 2nd and 3rd directions, the length of the sample separating chamber in the 3rd direction is larger than the length of the sample separating chamber in the 2nd direction, whereby, because one type of sample is handled by one centrifugal rotor, a discrete processing (sequential processing) suitable for a conveyor line production which can be performed independently of each other for each sample is enabled, and the automatization of sample preparation including the centrifugally separating operation can be facilitated.

/続葉有/

PCT/JP99/03341



WO 00/78464 A1

ABSTRACT OF THE DISCLOSURE

A centrifugal separator of the invention has a centrifugal rotor (10-1), with symmetric rotation axes, having single sample separation chamber in it for
5 centrifuging samples contained in sample solutions, an upper opening passing through to said sample separation chamber in the upper part, members of frameworks capable of being coupled to said upper opening, a rotation driving means, assuming that the direction of
10 said symmetric rotation axis is the first direction, for driving said centrifugal rotor around said rotation axis in the first direction, wherein assuming that two directions intersecting with said first direction are the second and third directions, the length of said
15 sample preparation chamber in said third direction is longer than the length of said sample preparation chamber in said second direction. Since one kind of sample is handled in one centrifugal rotor, the centrifugal separator of the invention allows discrete
20 treatment (sequential treatment) suitable for the flow system, in which individual samples can be treated independently, making easy automation of sample preparation revolving centrifugation.